

# MAGLUMI® X8

Fully Automatic Chemiluminescence Immunoassay (CLIA) System



# Outstanding Technologies Power of MAGLUMI®

### Chemiluminescence Immunoassay (CLIA) System

CLIA uses two important technologies, one is labelling technology which determines reaction mode, and the other is separation technology which determines the sensitivity, accuracy and precision of the reagents.

#### ABEI Labelling Technology

Two types of labelling technologies are commonly used. One is enzyme label and the other is non-enzyme small molecule label. Enzyme label reagents are not so stable and are easily affected by the change of storage conditions. MAGLUMI® system applies ABEI labels. ABEI is a non-enzyme small molecule with special molecular formula to enhance stability in acid and alkaline solutions. The chemical reaction process of ABEI with sodium hydroxide (NaOH) and hyperoxide (H<sub>2</sub>O<sub>2</sub>) finishes in 3 seconds.

#### Magnetic Microbeads Separation Technology

MAGLUMI® uses magnetic microbeads. As a separation technology, it has been widely used in the field of CLIA. Compared with traditional separation technologies, it has the following advantages,

- Shortening the reaction time by enlarging the reaction area of antigens and antibodies.
- Enhancing the sensitivity by better and faster capturing of antigens and antibodies.
- Reducing inter or intra-assay discrepancies significantly by mixing the reagents thoroughly in a liquid separation platform.



Reaction Module



Disposal TIP



Starter 1+2



Wash Concentrate



**Tubing Cleaning Solution** 



Light Check

# Advantages of MAGLUMI® X8



#### **High throughput**

- Throughput: up to 600 tests/hour(Single module)
- Up to 2400 tests/hour (Four modules combined)



#### **Excellent reliability**

- Magnetic microbeads separation , fast and efficient
- Flash chemiluminescence label-ABEI
- Intelligent magnetic field design ensuring excellent separation
- Disposable tips to prevent carry-over



#### **High capacity**

- Sample positions: 300
- Reagent Position: 42
- Up to 2800 walk-away tests



#### **Advanced intelligence**

- Capable to integrated several modules including Snibe Immunoassay, Biochemistry and ISE module
- Capable to link with Laboratory Automation System(TLA/LAS)
- User-friendly interface, easy operation
- Intelligent consumable loading technology
- Intelligent information monitoring system



## **MAGLUMI®**

- Flash chemiluminescence label-ABEI, with high sensitivity and long stability
- Magnetic microbeads separation, fast and efficient



#### **Sampling Loading**

- Up to 300 sample positions
- Continuous loading, STAT function available
- Auto remeasuring function, auto dilution function
- Sample editing mode:

Lis connection, barcode recognition, auto named, manual editing



#### Sample Transport System/Sampling System

- 3 channels, High speed loading
- Specific channel for STAT samples
- Disposable tips
- One pipetting for multiple tests
- Clot detection
- Liquid level detection
- Bubble detection
- Collision detection



#### Reagent Area

- 42 reagent positions on board
- Continuous loading
- RFID technology
- 24-hour refrigerated
- Working Temp. 8°C-12°C, Storage Temp. 2°C-8°C



#### **Reagent Needle**

- Titanium needle for crushproof
- Teflon coated for carry-over prevention
- Dual-arm design to pipette different reagents simultaneously
- Liquid level detection, Collision detection



#### **Tip Storage**

- Up to 576 TIPs loaded one time (6 boxes)
- Intelligent loading technology, continuous loading, real-time reserve monitoring



#### **Cuvette Storage**

- Single cuvettes design
- Up to 2912 cuvettes loaded one time (16 boxes)
- Intelligent loading technology, continuous loading, real-time reserve monitoring



#### **Consumable Management**

- Intuitive and concise design
- Intelligent reminding



#### **Software System**

- Brand new user-friendly UI interface
- Supporting SnibeLinker remote diagnosis system
- Multilingual support
- Touch screen, easy operation
- Report system including editing, storage, query and printing

# **Operation Software**





#### Comprehensive software

- User-friendly interface
- Real-time status monitoring for each test
- Monitoring reagent and consumable status
- Intelligent alarm function
- Multilingual support, more languages available by request



#### Maintenance guide

- Smart Maintenance with step by step guide, ensure performance reliability and reduce unnecessary service calls
- Daily, weekly and monthly maintenance guide for analyer



#### **Quality control**

 Westgard rules and Levey-Jennings chart for both internal and external quality control



#### **Test summary function**

- Test summary including system test, calibration, QC, statistics of samples, valid tests and rerun tests
- Search and review test information conveniently



#### Pre or post defined dilution function

• Pre- and post- dilution available for the case of high concentration sample



#### **Bidirectional LIS connection**

Bidirectional LIS connection by TCP/IP and ASTM

## **Test Menu**

#### **Thyroid**

TSH (3rd Generation)
T4
T3
FT4
FT3
Tg (Thyroglobulin)
TGA (Anti-Tg)
Anti-TPO
TRAb
TMA
Rev T3

#### **Hepatic Fibrosis**

HA PIIIP N-P C IV Laminin Cholyglycine \*GP73

\*T-Uptake

#### **TORCH**

Toxo IgG
Toxo IgM
Rubella IgG
Rubella IgM
CMV IgG
CMV IgM
HSV-1/2 IgG
HSV-1/2 IgM
HSV-1 IgG
HSV-2 IgG
\*HSV-1 IgM
\*HSV-2 IgM

#### **EBV**

EBV EA IgG EBV EA IgA EBV VCA IgG EBV VCA IgM EBV VCA IgA EBV NA IgG EBV NA IgA

## Inflammation Monitoring

CRP (High Sensitive)
PCT (Procalcitonin)
IL-6 (Interleukin 6)
SAA (Serum Amyloid A)
\*TNF-α

#### **Kidney Function**

β<sub>2</sub>-MG Albumin \*NGAL

#### **Fertility**

FSH LH HCG/β-HCG PRL (Prolactin) Estradiol Testosterone free Testosterone DHEA-S Progesterone free Estriol 17-OH Progesterone AMH SHRG Androstenedione \*PIGF \*sFlt-1

#### **Hypertension**

Direct Renin Aldosterone Angiotensin I Angiotensin II Cortisol ACTH

#### **Autoimmune**

Anti-CCP Anti-dsDNA IgG ANA Screen **ENA Screen** Anti-Sm IgG Anti-Rib-P IgG Anti-Scl-70 IgG Anti-Centromeres IgG Anti-Jo-1 IgG Anti-M2-3E IgG Anti-Histones IgG Anti-nRNP/Sm IgG Anti-SS-B IgG Anti-SS-A IgG TGA(Anti-Tg) Anti-TPO TRAb TMA **ICA** IAA(Anti Insulin) GAD 65 Anti-IA2 Anti-MPO \*ZnT8 \*Anti-Cardiolipin IgG \*Anti-Cardiolipin IaM \*β2-Glycoprotein I IgG

#### **Immunoglobulin**

\*β2-Glycoprotein I IgM

IgM IgA IgE IgG

#### **Tumor Markers**

AFP CEA Total PSA f-PSA CA 125 CA 15-3 CA 19-9 PAP CA 50 CYFRA 21-1 CA 242 CA 72-4 NSE S-100 **SCCA** TPA-snibe ProGRP HF4 HFR-2 PIVKA-II

#### **Infectious Disease**

HBsAg Anti-HBs HBeAa Anti-HBe Anti-HBc Anti-HCV Syphilis Anti-HAV HAV IgM HIV Ab/Ag Combi Chagas HTLV I+II H.pylori IgG H.pylori IgA H.pylori IgM 2019-nCoV IgG 2019-nCoV IgM SARS-CoV-2 S-RBD IgG SARS-CoV-2 Neutralizing Antibody SARS-CoV-2 Aq \*Anti-HBc IgM \*Chlamydia Pneumoniae IgG \*Chlamydia Pneumoniae IgM \*Mycoplasma Pneumoniae IgG \*Mycoplasma Pneumoniae IgM

#### Glyco Metabolism

C-Peptide
Insulin
GAD 65
Anti-IA2
ICA
IAA (Anti Insulin)
Proinsulin
\*Glucagon
\*ZnT8

#### Cardiac

CK-MB Troponin I Myoglobin hs-cTnI H-FABP NT-proBNP BNP D-Dimer Lp-PLA2 MPO \*HCY

#### **Coagulation Marker**

D-Dimer \*TAT \*TM \*PIC \*tPAIC

#### Metabolism

Pepsinogen I Pepsinogen II Gastrin-17 GH (hGH) IGF-I IGFBP-3

#### **Prenatal Screening**

AFP(Prenatal Screening)
Free β-HCG
PAPP-A
free Estriol

#### **Anemia**

Vitamin B12 Ferritin Folate (FA) EPO \*RBC Folate

#### **Drug Monitoring**

Digoxin CSA (Cyclosporine A) FK 506 (Tacrolimus)

#### **Bone Metabolism**

Calcitonin
Osteocalcin
25-OH Vitamin D
Intact PTH
β-CrossLaps (β-CTx)
total P1NP

\* Available soon

# MAGLUMI® X8

## Chemiluminescence Immunoassay (CLIA) System

#### **Technical Specifications**

#### **Reagent Features**

- Flash chemiluminescence label-ABEI, with high sensitivity and long stability
- Superparamagnetic microbeads separation technology; fast and efficient

#### **Main Features**

- Throughput: up to 600 tests/hour (Single module)
- Time to first result: 15 minutes
- 24 hours ready to use
- Up to 2800 walk-away tests
- Modular Expanding Flexibility:
  - \*Capable to integrated several modules including Snibe Immunoassay, Biochemistry and ISE module
- \*Capable to link with Laboratory Automation System (TLA/LAS)

#### Sample Loading

- Up to 300 sample positions
- Continuous loading, STAT available
- · Auto remeasuring function
- Sample editing mode:
   Lis connection, Barcode recognition, Auto named, Manual editing

#### **Reagent Loading**

- 42 reagent positions on board
- Continuous loading
- RFID technology
- 24-hour refrigerated
- Working Temp. 8°C-12°C, Storage Temp. 2°C-8°C

#### **Reagent Needle**

- Titanium needle for crushproof
- Teflon coated for carry-over prevention
- Dual-arm design to pipette different reagents simultaneously
- Liquid level detection, Collision detection
- Probe depth adjustment automatically

#### **Reagent Integral**

- Ready to use, no pretreatment required
- Calibrators and internal controls included
- RFID tag storing all info of reagent
- 2-point re-calibration
- Calibration stability: up to 4 weeks
- Storage temperature: 2°C-8°C

#### **Sampling System**

- Using disposable TIPs
- One pipetting for multiple tests
- Clot detection
- Liquid level detection
- Bubble detection
- Collision detection

#### **Reaction Disk**

- Incubating 252 cuvettes simultaneously
- Stable 37.0 ± 0.3°C incubation
- Non-contact mix technology

#### **Tip Storage**

- Up to 576 TIPs loaded one time (6 boxes)
- Intelligent loading technology, continuous loading, real-time reserve monitoring

#### **Cuvette Storage**

- Single cup design
- Up to 2912 cuvettes loaded one time (16 boxes)
- Intelligent loading technology, continuous loading, real-time reserve monitoring

#### Washer

- 4-step washing technology, high speed single channel design
- Intelligent magnetic field design ensuring excellent separation
- Non-contact magnetic microbeads suspension technology

#### **Software System**

- Bidirectional LIS connection by TCP/IP and COM Port
- Supporting SnibeLinker remote diagnosis system

#### **Dimensions Weight**

- Input: AC 100-240V,50/60Hz
- Dimensions and Weight:192\*118\*150 (cm), 670Kg



Shenzhen New Industries Biomedical Engineering Co., Ltd. (SNIBE Co.,Ltd.)

No.23, Jinxiu East Road, Pingshan District, 518122 Shenzhen, P.R. China

Tel: +86 755 26501514 Email: sales@snibe.com

com Web: www.snibe.com

Fax: +86 755 26654850





